



## NEXUS® UVI TECHNICAL DATA SHEET

			<b>17.8 Micron</b>	<b>22.9 Micron</b>
Thickness	ASTM D-4649	Gauge	70(17.8)	90(22.9)
Puncture Force	ASTM D-5748	Pounds	6.3	7.3
Tensile Ultimate MD	ASTM D-882	PSI	5390	5490
Tensile Ultimate CD	ASTM D-882	PSI	5180	5400
Tensile Yield MD	ASTM D-882	PSI	1365	1440
Tensile Yield CD	ASTM D-882	PSI	1365	1400
Elongation at MD	ASTM D-882	%	460	480
Elongation at CD	ASTM D-882	%	630	650
Unstretched Cling	ASTM D-4649	Grams (g)/in	179	166

*All values are representative of typical film performance and are not to be construed as manufacturing and/or sales specifications.*

*Paragon Films UVI products are formulated and tested to provide at least six months of protection under most conditions; however, many variables impact the integrity of stretch film in outdoor conditions. PARAGON FILMS DOES NOT GUARANTEE UVI PROTECTION AND SPECIFICALLY DISCLAIMS ALL EXPRESS OR IMPLIED WARRANTIES INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.*